

Curve

CB Wi-Fi call buttons



Connect customers with staff
for discreet and rapid response.

Increased safety and satisfaction

Compatible with Curve and DLR radios, and Digital Hub, the CB Wi-Fi call buttons connect customers directly to employees. So when a customer presses a call button for assistance, employees can more efficiently and discreetly respond - no PAs necessary.



Key features

Shopper-friendly

Single-button operation

Flexible to fit inside your workflow

Wi-Fi based, with 4 different form factors

Attention-grabbing

Assurance LED and message when a shopper presses HELP

Programmable escalation rule

Hub can reroute messages to an escalation channel for immediate management response

Today's customer is aware and self-sufficient, desiring quick assistance and safe environment. The Curve Ecosystem is the evolution of customer service, enabling staff to prioritize the customer with organized urgency. When a customer presses the button for assistance - in-store or curbside - the Curve Digital Hub sends an alert to your Curve or DLR radio fleet. Employees can then respond without using the PA system. Call button behaviors (the number of presses, response times, date, location and more) can be analyzed and managed on the Curve Portal, where you can also remotely configure repeat and escalation notifications.





GENERAL SPECIFICATIONS

Model	CB401: Glass mount Wi-Fi call button
	CB402: Blade style Wi-Fi call button (without blade)
	CB403C: Countertop mount Wi-Fi call button
	CB403W: Wall mount Wi-Fi call button
Frequency band	2.4 GHz + 5 GHz Wi-Fi
Wi-Fi standards supported	2.4 GHz 802.11b/g/n 5 GHz 802.11a
Regulatory	EN 300 328, EN 301 489, EN 301 893 and EN 303 489
Packaging	White box
Warranty	1 year

DIMENSIONS

H x W x D without base	CB401: 72 x 72 x 27.5mm
	CB402: 72 x 72 x 80mm
	CB403C: 98.5 x 98.5 x 56mm
	CB403W: 98.5 x 98.5 x 56mm
Weight including battery	CB401: 113g
	CB402: 142g
	CB403C: 160g
	CB403W: 160g

ENVIRONMENTAL

Operating temperature	0° C to 49° C
Storage temperature	-20° C to 60° C
Location	Indoor use

ENERGY

Battery life	2-3 years ¹
Nominal voltage	3V DC
Battery capacity	3V DC with lithium CR17345
No. of batteries	2

¹Based on 6-10 button presses per day



For more information, please visit motorolasolutions.com/curve

Motorola Solutions, Inc. 10 Wesley Court, Burwood East, Victoria 3151, Australia. motorolasolutions.com

MOTOROLA, MOTOTRBO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2024 Motorola Solutions, Inc. All rights reserved. (05-24)